



SPECIFICATIONS

BETWEEN FRAMES: 15" - 51"	LENGTH: 24" - 120"
ROLLER CENTERS: 3", 4.5", 6"	
ROLLERS: 1912 Roller - 12ga wall tube. 1916 Roller - 16ga wall tube. All rollers 1.9" dia, with 7/16" hex cold rolled steel axles, spring retained. <u>Standard</u> bearings are light oil lubricated. <u>Optional</u> bearings include combinations of precision, semi-precision and non-precision construction with light oil or grease packed lubrication .	
FRAMES: Standard F70 set high 5" x 1-1/2" x 12ga formed steel channel with bolted 1-1/8" x 1/8" angle crossties. <u>Optional</u> F71 set low 6" x 1-1/2" x 12ga.	
ROLL COVERS: Standard carbon steel. <u>Optional</u> roll covers includes Orange Polyurethane, 1/8" wall or galvanized tube.	
CASTERS: 4" cast iron V-groove and 5" phenolic.	
HANDLE: 1" pipe with hand grip.	
END STOP: Fixed style, near handle.	
FRAME FINISH: Standard finish is OSHA safety blue powder. <u>Optional</u> colors include green, beige, gray, orange, black and yellow.	

Model: TC1912, TC1916 - Transfer Conveyor, 1.9 diameter

REV
0

